

APPROVAL SHEET PRODUCT NAME CUSTOMER APPROVED BY DAM1575A4X4_JW5M CUSTOMER NAME OR MODEL APPROVED DATE

SPECIFICATION

Product Name: DAM1575A4X4_JW5M

Description: 2.7~5V/10mA(at 3V)/27dB/500cm

(Typical Value)

VERSION INFORMATION

VERSION	DATE	REVISION DES	SCRIPTION	PREPARED	CHECKED	APPROVED
V1.0	2010/06/29	NEW ISS	SUED	Mark Yan	Sheng Gao	Garvin Ge
		F	RoHS Compli	ant Parts		
			1			

NOTE:

- 1. When to change the electrical performance index, have to change the relevant version the same time.(As to change V1.0 into V2.0, V3.0....);
- 2. When to change the testing mothed(including the reliability testing conditions),or to change the operation condition, have to add number to present version(As to change the V1.0 into V1.1, V1.2.....).

PREPARED BY	CHECKED BY	APPROVED BY
Mark Yan	Sheng Gao	Garvin Ge

Jiaxing Glead Electronics Co., Ltd

No.66 Zhengyuan Road, Jiaxing City, Zhejiang Province, China



PRODUCT SPECIFICATION

Product Name	Prepared date	Page
DAM1575A4X4_JW5M	2010.06.29	2/6
Prepared by	Checked by	Approved by
Mark Yan	Sheng Gao	Garvin Ge

1. Electrical Characteristics			
1.1 Antenna			
1	Antenna model	DAS1575(25*25*4)	
2	Frequency Range	1575.42MHz±1.023 MHz	
3	V.S.W.R	1.5:1	
4	Band Width	> 10 MHz	
5	Impendence	50 ohm	
6	Gain	5dBic Based on 70×70mm ground plane	
7	Polarization	RHCP	
1.2 LNA			
1	Frequency Range	1575.42MHz±1.023 MHz	
2	DC Voltage	3.0~5.0V	
3	Gain (Typical)	27±2dB (Without cable +25°C±10°C)	
4	Output VSWR (Typical)	2.0	
5 Noise Figure (Typica		1.3 (+25°C ±10°C, at 1.3V)	
6	DC current (Typical)	10mA(At 3.0V)	


2. Material			
No	Part Name	SPEC	
1	Antenna	Dielectric Ceramics	
2	PCB	FR4	
3	Shielding	Tinplate	
4	RF Cable	RG174	
4		L=500±10cm	
5	RF Connector	MCX	
6	Thickness	About 15mm	

Jiaxing Glead Electronics Co., Ltd
No.66 Zhengyuan Road, Jiaxing City, Zhejiang Province, China



Product Name	Prepared date	Page
DAM1575A4X4_JW5M	2010.06.29	3/6
Prepared by	Checked by	Approved by
Mark Yan	ShengGao	Garvin Ge

3. Smith chart of patch antenna




Test condition:70x70mm ground

No.66 Zhengyuan Road, Jiaxing City, Zhejiang Province, China



Product Name	Prepared date	Page
DAM1575A4X4_JW5M	2010.06.29	5/6
Prepared by	Checked by	Approved by
Mark Yan	Sheng Gao	Garvin Ge

4. LNA testing curve (Testing condition: DC 3.0V)




Jiaxing Glead Electronics Co., Ltd

No.66 Zhengyuan Road, Jiaxing City, Zhejiang Province, China



Product Name	Prepared date	Page
DAM1575A4X4_JW5M	2010.06.29	5/6
Prepared by	Checked by	Approved by
Mark Yan	Sheng Gao	Garvin Ge

5. Structure and reference picture



Tolerance. ±0.5

Unit: mm

Jiaxing Glead Electronics Co., Ltd


No.66 Zhengyuan Road, Jiaxing City, Zhejiang Province, China



Product Name	Prepared date	Page
DAM1575A4X4_JW5M	2010.06.29	6/6
Prepared by	Checked by	Approved by
Mark Yan	Sheng Gao	Garvin Ge

6. Environment Condition		
1	Working Temp	-40°C∼+80°C
2	Storage Temp	-45°C~+85°C
3	V:1	Sine sweep 1g(0-p)
	Vibration	10~55~10Hz each axis

7. Notes





- 2. This product specification guarantees the quality of our product as a single unit. Please make sure that your product is evaluated and confirmed against your specifications when our product is mounted to your product.
- 3. The product will get free warranty for three months since the date of purchase users operate in the correct way; users will have to pay cost of the materials and maintaining fee out of the condition.

8. Packing

Each pearl cotton box includes 1 PCS antenna and 1 set accessories the size of box is 370 * 300 * 100 mm.



Jiaxing Glead Electronics Co., Ltd

No.66 Zhengyuan Road, Jiaxing City, Zhejiang Province, China